

## AGB01



Ceiling ( Red ) Basic duration 120 cd/ $\mbox{m}^{2}$ 

## AGB01



Wall Mount ( White ) Basic duration 120 cd/ $\mbox{m}^{2}$ 

## AGB02



Wall Mount ( Red ) Basic duration 120 cd/ $\mbox{m}^{2}$ 

## **Product Overview**

AGB01 and AGB02 Fire Strobe Light utilizes super bright LEDs which generates a high-intensity light, visible from all sides of the lens to provide a visible notification signal for the purpose of life safety and property protection and it can connect synchronizer, thereby synchronizing with other bands of visual fire alarm. It is ideal to be installed at hotels, apartments, hospitals, commercial buildings, residential buildings, shopping malls or wherever visible alarms are required.

Having considered power saving for the fire alarm system, we adopted the best quality LEDs, which consume less current while maintaining the brightness comparable to the traditional Xenon strobe does. Besides, customers can also save on material costs by slashing the battery and the battery charger size. For facilitating the wiring work, our strobes can achieve self synchronization through power cables and no additional signal cables or equipment are required.

	10004/4000
Model	AGB01 / AGB02
Description	LED visual fire alarm
Voltage (with limit+/-15%)	DC18V~DC28V
Light Output in candela	120 cd/m <sup>2</sup>
Light Output in Colour	Red
Lens Colour	Red / Transparent
Current Draw	31mA / 0.754W
Peak Current Draw	35mA
Flash Frequency	60 pulses/minute,1 Hz
Synchronized function	In-built circuitry self-synchronized
Connection/device to achieve Synchronization	No Module / synchronizer / control cable required
Operating Temperature	-10℃~65℃
IP Rating-*IP65 models labeled with ( wp )	Standard weatherproof to BS5490 IP54/55,Special
Following the standard model number	Request for *IP65(additional weatherproof lens
	fitted ring and in sealed type)
Dimensions	AGB01:126 x 85 x 55 mm (L x W x H)
	AGB02:140 x 130 x 60mm(L x W x H)
Standard Specifications	Clause 9.7 of BS5839 Part 1:1988,EN54-23:2010,
CCIC test certificate	HKFSD circular 4/2001 point 3.(ii)and 4.(i)(ii)(iv)
Installation	Wall or ceiling mounted
Brand Name	ATM
Product Origin	China – Hong Kong